

EQUIPE

ALUMINIUM
PROFESSIONAL
INTENSIVE USE





EQUIPE is a telescopic ladder in aluminium, can be used in extended, double or adjustable position. Its main strengths make it unique in the market: patented galvanized steel hinge with three pins, eliminates the use antiopening belt; rungs 30x30 mm, thickness 1.50 mm, 60x25 mm internal section, 68x33 mm external section. Pitch between the rungs 280 mm. Angle of aperture designed to a comfortable working position, allows the support of the body safely.



- Quick coupling
- 3 pins to ensure a safe lock
- Open and close without repositioning the handle.

Galvanized steel safety block, Nylon coated



Anti slip knurled, strengthened rung, size 30x30 mm, thickness 1.50 mm, welded with robotic system CMT (cold metal transfer).

Rungs
mm 30X30



EQUIPE



mm 30X30



+ POSITIONS



Extended



Adjustable double



Open and close



Mandatory stabilizers for ladders higher than m 3,00.



Ladder dimensions



Total load permitted



Kg 150

CODICE D.LGS. 81/08 +EN 131-4:2020	ART.													
		6+6	0,96	2,83	2,95	1,45	0,90	482	mm	mm	Kg	vol. mc	€	EAN
  20431	EQU33										10,00	0,09		8021227004000
  20710	EQU34										12,40	0,10		8021227005564
  20029	EQU44										14,00	0,12		8021227001672
  20030	EQU45										15,00	0,14		8021227001689
  20031	EQU55										16,60	0,15		8021227001696
 20506	EQU66										19,20	0,20		8021227002754